



IF IN DOUBT ASK
DO NOT SCALE

ø3.6-8 HOLES
(SEE NOTE)



HORIZONTAL PANEL CUT-OUT(E12/E16).
FOR VERTICAL CUT-OUT, ROTATE THRO' 90°

25mm MIN CLEARANCE FOR TERMINAL WIRING
70mm MIN CLEARANCE FOR F/O COMMS CABLE

DRAWING OFFICE ONLY NOTE

ANY CHANGE TO THIS DRG MUST BE
REFLECTED ON DRGS 2995X10012,2995X10016,
& CATALOGUE.

	E12 CASE		E16 CASE
V	286	V	364
W	9.25	W	21.75
X	304.5	X	407.5
Y	104	Y	182
Z	311.5	Z	415.5

NOTE:

THE ø3.6 HOLES ARE FOR M4 THREAD FORMING (TRILOBULAR) SCREWS. THESE ARE SUPPLIED AS STANDARD AND ARE SUITABLE FOR USE IN FERROUS/ALUMINIUM PANELS 1.6mm THICK AND ABOVE. FOR OTHER PANELS, HOLES TO BE M4 CLEARANCE (TYPICALLY ø4.5) AND RELAYS MOUNTED USING M4 MACHINE SCREWS, NUTS AND LOCKWASHERS (SUPPLIED IN PANEL FIXING KIT).

**NOT SUBJECT TO UPDATE
ONCE COPIED / PRINTED
OR DOWNLOADED**

3	RDW	23/05/03	MN995/2531 MM
2		21/1/03	MN995/2462 ML
1		26/7/01	CHANGE
ISSUE	DATE		NOTED

Copyright © 2001 Reyrolle Ltd.

MATERIAL:

Dimensions in millimetres ; Surface texture in micrometres.
Machine where marked ✓
For explanation of dimensions, tolerances, notes etc. see B.S.308.
Limit on untoleranced unmachined dimensions ± _____
Limits on untoleranced machined dimensions to B.S.4500;
i.e. up to 6±0.1; over 30 to 120±0.3; over 315±0.8;
over 6 to 30±0.2; over 120 to 315±0.5;
General unmachined angular tolerance ± _____

Finish: _____
Treatment: _____

Title:
OVERALL DIMENSIONS AND PANEL DRILLING
FOR EPSILON E12 & E16 CASES

**Reyrolle Protection
Hebburn.**

Original Scale:
NTS

First used on:
Similar Articles:
Supersedes:
Drg.No.
2995X10018

DRAWN: M LEASK	CHECKED:	APPROVED: R.D.WATSON	DATE: 11/07/02	I.E.	OPS.	PCP.	Purch. Spec.	TQ.	EAC	CE.	STD.	A4h
----------------	----------	----------------------	----------------	------	------	------	--------------	-----	-----	-----	------	-----